



Model	TLM-170P/PM/PR	TLM-170L/LM/LR	TLM-702HD
			
面板	17.3" LED Back-Lit	17.3" LED Back-Lit	2x7" LED Back-Lit
外觀	Tabletop (170P) 1RU Pull-Out (170PM) 7RU Rack Mount (170PR)	Tabletop (170L) 1RU Pull-Out (170LM) 7RU Rack Mount (170LR)	3RU Rack Mount
解析度	1920x1080	1920x1080	800x480
可視角度	(H) +80/-80° (V) +60/-80°	(H) +70/-75° (V) +60/-60°	(H) +70/-70° (V) +50/-70°
亮度/對比	400cd/m <sup>2</sup> 600:1	300cd/m <sup>2</sup> 400:1	300cd/m <sup>2</sup> 500:1
影像輸入	1x 3G/HD/SD-SDI 2x HDMI 1x HD/SD-YUV 2x Composite Video	1x 3G/HD/SD-SDI 2x HDMI	2x HD/SD-SDI 2x HD/SD-YUV 2x HDMI 2x Composite Video
環通輸出	1x 3G/HD/SD-SDI 1x Composite Video	1x 3G/HD/SD-SDI	N/A
支援影像格式	1080p(23.98/24/25/30/50/59.9 5/60Hz), 1080i(50/59.94/60Hz), 720p(50/59.94/60Hz), 480i (NTSC), 576i (PAL)	1080p(23.98/24 SF/24/25/29.97/30/50/59.9 5/60Hz), 1080i(50/59.94/60Hz), 720p(50/59.94/60Hz), 480i (NTSC), 576i(PAL)	1080i(50/60Hz), 720p(50/60Hz) 480i(NTSC), 576i(PAL)
顯示模式	16:9, 4:3	16:9, 4:3	16:9, 15:9, 4:3
Tally模式	Live (Red) Cued (Green)	Live (Red) Cued (Green)	Live (Red) Cued (Amber)
聲音輸入/輸出	Embedded Audio on SDI and HDMI 3 x Mono RCA Inputs Stereo Speakers	Embedded Audio on SDI and HDMI	Embedded Audio on SDI and HDMI Audio Level Indicator 2x Stereo Headphone Jack
特別功能	3G-SDI Support, Picture-in-Picture, Blue Only, Audio Level Indicator, Safe Frame, Pixel Zoom up to 8x, Network IP Remote, SDI Time Code Display	3G-SDI Support, Blue Only, Safe Frame, Pixel Zoom up to 8x	Blue Only, Safe Frame, SDI Time Code Display, Audio Level Indicator, Safe Frame
電源	DC 12V, 30 watts	DC 12V	DC 12V, 30 watts