

SD 4.3 吋液晶監視器

TLM-430



內建 Tally 燈之回看螢幕

Datavideo TLM-430 之 4.3 吋回看監視螢幕，有大燈號顯示的 Tally 燈，重量不到 210 公克，安裝在攝影機上不會造成攝影機重量不平衡，同時讓使業務級攝影機的多機作業的攝影人員，可切換攝影與導播主輸出之影像監看。

HD/SD 7 吋液晶監視器

TLM-700HD



Model	Description
TLM-700HD-C	TLM-700H w/ Canon Battery Mount (compatible with Canon BP series DV batteries)
TLM-700HD-A	TLM-700H w/ Anton Bauer Battery Mount (Gold mount plate with a 14.4V D-tap output socket for Gold mount battery applicable)
TLM-700HD-P	TLM-700H w/ Panasonic Battery Mount (compatible with Panasonic CGA series DV batteries.)
TLM-700HD-S1	TLM-700H w/ Sony Battery Mount (S-7000U) (for SONY EX1 / EX3 camcorder's battery/ compatible with SONY BP-U60, BP-U30 DV batteries)
TLM-700HD-S2	TLM-700H w/ Sony Battery Mount (S-7000F) (e.g For SONY Z5 camcorder's battery/ compatible with SONY NP-F770/970/960/950 DV battery applicable)



TLM-700HD 監視螢幕可接受 SD 與 HD 雙影像訊號格式，可外掛各品牌攝影機電池，協助戶外作業時電源取需求。

Model	TLM-700HD	TLM-434H	TLM-430
面板	7" LED Back-Lit	4x4.3" TFT LCD	4.3" TFT LCD
外觀	Camera Mount	2RU Rack Mount	Camera Mount
解析度	800x480	480x272	480x272
可視角度	(H) +70/-70° (V) +50/-70°	(H) +80/-80° (V) +80/-80°	(H) +70/-70° (V) +50/-70°
亮度/對比	300cd/m ² 500:1	320cd/m ² 400:1	500cd/m ² 500:1
影像輸入	1x HD/SD-SDI 1x HD/SD-YUV 1x HDMI 1x Composite Video	4x HD/SD-SDI 4x HDMI	2x Composite Video
環通輸出	N/A	4x HD/SD-SDI	N/A
支援影像格式	1080i(50/60Hz) 720p(50/60 Hz) 480i(NTSC) 576i(PAL)	1080i(50/60Hz) 720p(50/60 Hz) 480i(NTSC) 576i(PAL)	480i(NTSC) 576i(PAL)
顯示模式	16:9, 15:9, 4:3	16:9, 4:3	16:9, 4:3
Tally 模式	Live (Red) Cued (Amber)	Live (Red) Cued (Amber)	Live (Red) Cued (Green)
聲音輸入/輸出	Embedded Audio on SDI and HDMI Audio Level Indicator, 1x Stereo Headphone Jack	Embedded Audio on SDI and HDMI, Audio Level Indicator, 4x Stereo Headphone Jack	N/A
特別功能	Blue Only, Safe Frame, SDI Time Code Display, Audio Level Indicator, Safe Frame, Image Flip, Can powered by batteries (Not Included)	Blue Only, Embedded Time Code Indicator, Safe Frame	Can be powered by DC adaptor, Sony batteries or D-TAP. TLM-43LB Camera look back system (with RMC-200 and control cable)
電源	DC 12V, 18 watts	DC 12V, 15 watts	DC 12V, 6 watts